

FEATURES LIST

STANDARD FEATURES

Sidestance operator controls
Operator sensing system
Wire mesh mast guard
EZ Ride floor
Low profile anti-fatigue floormat
Automotive steering
Steer tiller position adjustment
24 Volt battery (includes 350 amp red battery connector)
91" / 203" / 52" – (5.5") 3 Stage full free lift mast
Single reach mast (24" extend) with 33.5" wide class II with integral sideshift (hook type carriage)
Double reach mast (42" extend) with 33.5" wide class II with integral sideshift (hook type carriage)
Forks: 1.8" x 3.9" (45 mm x 100 mm) 42" (1067 mm) – class II, hook type (standard on NR040DC)
Forks: 1.6" x 3.9" (40 mm x 100 mm) 42" (1067 mm) – class II, hook type (standard on NDR030DC and NR035DC)
5" x 3.9" Poly articulating tandem load wheels - high load compound (standard on NR035DC and NR040DC)
5" x 2.9" Poly articulating tandem load wheels - high load compound (standard on NDR030DC)
AC traction, lift / lower and steering
Low step height
Transistor controller with regenerative braking
4 Independent fully programmable performance modes
Programmable traction speed and acceleration
Electric power steering
Fully proportional lift/lower control
Poly drive tire – 13.5" x 5.5"
Dual articulating polyurethane caster wheels
Power disconnect
Key start
2 USB ports
36" High load backrest extension
Sealed battery rollers
Tilting carriage (3° fwd, 4° back)
Padded operator compartment
Rear post operator protection
Operator's overhead guard
Control handle with simultaneous hydraulic functions
5" Smart display: color touchscreen with:
– Clock
– Bar graphic battery discharge indicator and lift interrupt
– Hour meters: truck, traction, hoist pump, and secure
– Maintenance reminder
– Programmable performance mode selection
– User passwords and operator logs with history
– Steer wheel angle graphic indication
– Truck inspection check list
– Truck speed indication in MPH or KPH
Electronic horn
Static discharge strap
UL classification E
Operating manual
12 Month / unlimited hours full truck warranty
3 Years/ 6,000 hour powertrain warranty
Lifetime frame warranty

OPTIONAL FEATURES

Fore/aft stance operator controls
Reverse steering
Yale® Smart Ride Floor (full suspension floor)
Clear mast guard
Steered caster - SPED
Keyless start
7" Smart display: color touchscreen
Rotary joystick (opt – standard construction, standard – cooler/freezer)
36 Volt battery (includes 350 amp gray battery connector)
Battery stand
Battery puller
Battery gate interlock
Lithium ion ready
Fuel cell ready
Cooler/freezer construction (0° F to 120°F), includes rubber floormat
Various-sized load wheels with sealed bearings
Various drive tires
Tapered load wheel boxes
Lift limits
Single reach mast without integral sideshift for standard 33.5" wide carriage-7" total sideshift travel **
Various fork lengths
Various I.D. outriggers
Fork height display
48" High load backrest extension
Audible back-up and motion alarms
Visual amber strobe light
Blue LED spotlights
Operator LED desktop light
Dual LED headlights
Rear LED worklight
Operator overhead fan
Load weight display
Reduced travel speed with carriage extended
RF terminal bracket
RF Handheld scanner holder
12 Volt DC auxiliary power supply
Impact monitor
Wire mesh on top OHG
Parts manual
Rear operator compartment door * - SPED
Yale Vision

** Doors are intended to protect the operator from objects that may enter the operator's compartment but they may also slow the operator's egress in emergency situations. A review of the forklift's intended environment should be conducted before selecting a door as optional equipment.*

*** Sideshift includes 7" travel (3.5" each side). Sideshift travel will be reduced to 3" total (1.5" each side) when Outrigger ID is less than 39".*